



Mylar[®]
Specialty Films

Polyester Films for Electrical Insulation



The industry standard for electrical insulation

For over sixty years, Mylar® and Melinex® polyester films have been key components in electrical insulation systems and provide the ideal solution for various industry sectors such as Renewable Energy, Automotive, Industrial Equipment, Household, Lighting & Cable.

For applications that need electrical insulation systems offering high reliability and long service life, Mylar® A is the industry standard polyester film providing the optimum combination of mechanical strength, thermal resistance and durability. Mylar® A is available in the thickness range of 23 to 350 micron from our manufacturing plants in the UK, USA and China.

Good Balance of Mechanical Properties

- A strong tough material which is suitable for mechanical forming and allows easy roll to roll lamination

Superior thermal performance with resistance to temperature peaks up to 150 °C

- Making suitable for motors operating at elevated temperatures

Underwriter Laboratories Recognition

- QMFZ2-E92687
- QMFZ2-E523642

High Dielectric Strength

- Breakdown voltage of 23kV at a thickness of 250 micron

Chemically Resistant


- Excellent resistance to solvents and resins commonly used in the production of electrical laminates and machines

Kaladex® PEN Films in electrical insulation

Kaladex® PEN films can be handled and processed in a similar way to more familiar films based on polyethylene terephthalate (PET), but the distinct polymer chemistry of PEN provides several superior properties including greater resistance to heat and hydrolysis, better dimensional stability and higher modulus. Kaladex® PEN has an RTI suitable for use in Class F (155 °C) applications, with the possibility of use as a system component at higher classes

The main grade used in electrical insulation applications is Kaladex® 2000 which exhibits the following key features:

- Elevated RTIs of 160 °C mechanical and 180 °C electrical under UL746B (File E93687)
- Good mechanical strength with stiffness 25% higher than PET
- Excellent dielectric strength (typically 8 x aramid paper)
- Good thermal conductivity (2 x aramid paper at same thickness)
- Greater hydrolysis resistance compared to standard PET
- Low moisture absorption
- Excellent solvent resistance
- Very low oligomer extraction in



Range of Films for electrical insulation applications

Film Type	Thickness Micron (gauge)	Film Description
Mylar® A	23, 36, 50, 75, 100, 125, 190, 250, 300, 350 (92, 144, 200, 300, 400, 500, 760, 1000, 1200, 1400)	Milky white film with high dielectric strength, temperature durability and dimensional stability
Mylar® ADS	50, 75 (200, 300)	Low shrink version of Mylar® A. Suitable for FPC and MTS circuitry. Other thicknesses possible subject to a suitable commercial case.
Melinex® 238	75, 125, 190, 250, 350 (300, 500, 760, 1000, 1400)	Milky white film with low oligomer content and superior thermal performance specifically for insulation in hermetic compressor motors
Kaladex® 2000	16, 25, 38, 50, 75, 100, 125 (64, 100, 152, 300, 400, 500)	High performance polyethylene naphthalate (PEN) film with UL-recognised RTIs of 160 °C mechanical and 180 °C electrical, suitable for use in Class F (155 °C) applications with the possibility of use as a system component at higher classes.



www.mylar.com

contact us: europe@mylar.com / usa@mylar.com / ap@mylar.com

United Kingdom

Mylar Specialty Films UK Ltd
The Wilton Centre
Redcar
TS10 4RF

Continental Europe

Mylar Specialty Films Luxembourg SA
BP-1681
L-1016
Luxembourg

United States

Mylar Specialty Films
3600 Discovery Drive
Chester
VA 23836 USA

Asia Pacific

Mylar Specialty Films
Room 702, 7th Floor, China Life Center
Tower A, One Harbour Gate,
No.18 Hung Luen Road, Hon Hom,
Kowloon, Hong Kong

This information corresponds to our current knowledge on the subject. It is offered solely to provide possible suggestions for your own experimentations. It is not intended, however, to substitute for any testing you may need to conduct to determine for yourself the suitability of our products for your particular purposes. This information may be subject to revision as new knowledge and experience becomes available. Since we cannot anticipate all variations in actual end-use conditions, Mylar Specialty Films makes no warranties and assumes no liability in connection with any use of this information. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent right. © 2024 Mylar Specialty Films. All rights reserved, all trademarks and service marks denoted with ™ or ® are owned by Mylar Specialty Films or associated affiliates unless otherwise noted. Nothing contained herein shall be construed as a representation that any recommendations, use or resale of the product or process described herein is permitted and complies with the rules or regulations of any countries, regions, localities etc or does not infringe upon patents or other intellectual property rights of third parties. Melinex®, Mylar® and Kaladex® are registered trademarks of Mylar Specialty Films U.S. Limited Partnership.